



54, Annapurna Industrial Estate, Tilak Road,
Ghatkopar (E), Mumbai - 400 077 India
Tel: +91-22-21029911
E-mail: sales@excellaelectronics.com



SWITCH MODE POWER SUPPLY (SMPS)

TECHNICAL SPECIFICATION

MODEL	EES12V6A
INPUT	
I/P	230V AC, 1-Ph
Frequency	47-63HZ
Range	180-270V AC
Fuse Protection.	Yes
I/P MOV	Yes
Soft Start	Yes
Inrush current	46A@230V AC
AC Current	
Leakage Current	< 5mA@230V AC
OUTPUT	
Nominal Voltage	12V DC
Voltage Range	12-15V
Rated Current	6A
Line Regulation	+/- 1%
Load Regulation	+/- 1%
Ripple Max (P-P)	+/- 1%
Noise Max (P-P)	+/- 1%
Protections	a) Overload Protection auto recovery type:102-105% b) Short circuit protection auto recovery type:Yes c) Over Voltage Protection Latching type:105-110%
Current Limit.	Yes
Start up time	1.2 sec
Hold up time	82ms
ENVIRONMENTAL	
Operating temperature upto 50° C.	
Humidity	< 95% Rh
IP 21 Protection	
GENERAL	
Isolation	Input to Output – 1.5KV Input to Earth – 1.5KV Output to Earth- 500V
MTBF	50K Hrs to MIL
INDICATIONS LED	a) Input OK b) Output OK c) Output OVP
MECHANICAL	
Dimension	165W X 105D X 60H mm
Cooling type	Natural
Weight	0.8 Kg
OPTIONAL	
Redundancy by external diode.	