



54, Annapurna Industrial Estate, Tilak Road,  
Ghatkopar (E), Mumbai - 400 077 India  
Tel: +91-22-21029911  
E-mail: sales@excellaelectronics.com



Mfg. Of Motion Control Devices &  
Specialize in Elevator Automation Products

## SWITCH MODE POWER SUPPLY (SMPS)

### TECHNICAL SPECIFICATION

#### MODEL

EES8V4A

#### INPUT

I/P	230V AC, 1-Ph
Frequency	47-63Hz
Range	90-270V AC
Fuse Protection	Yes
I/P MOV	Yes
Soft Start	Yes
Inrush current	23A@230V AC
AC current	
Leakage current	<5mA@230V AC

#### OUTPUT

Nominal Voltage	8V DC
Voltage Range	7-9V
Rated Current	4A
Line Regulation	+/- 1%
Load Regulation	+/- 1%
Ripple Max (P-P)	+/- 1%
Noise Max (P-P)	+/- 1%
Protections	

b) Short circuit protection auto recovery type:Yes  
a) Overload Protection auto recovery type:102-105%

Current Limit.	Yes
Start up time	750ms
Hold up time	37ms@230V AC

#### ENVIRONMENTAL

Operating temperature upto 50° C.	
Humidity	< 95% Rh
IP 21 Protection	

#### GENERAL

Isolation	Input to Output – 1.5KV Input to Earth – 1.5KV Output to Earth- 500V
MTBF	50K Hrs to MIL
Efficiency	70%

#### INDICATIONS LED

a) Input OK  
b) Output OK  
c) Output OVP

#### MECHANICAL

Dimension	135W X 90D X 50H mm
Cooling type	Natural
Weight	0.5 Kg

#### OPTIONAL

Redundancy by external diode.