



SWITCH MODE POWER SUPPLY (SMPS)

TECHNICAL SPECIFICATION

MODEL	EES5V6A
INPUT	
I/P	230V AC, 1-Ph
Frequency	47-63Hz
Range	90-270V AC
Fuse Protection	Yes
I/P MOV	Yes
Soft Start	Yes
Inrush current	23A@230V AC
AC Current	
Leakage Current	< 5mA @230V AC
OUTPUT	
Nominal Voltage	5V DC
Voltage Range	5-5.5V
Rated Current	6A
Line Regulation	+/- 1%
Load Regulation	+/- 1%
Ripple max (P-P)	+/- 1%
Noise max (P-P)	+/- 1%
Protections	a) Overload Protection auto recovery type:102-105% b) Short circuit protection auto recovery type :Yes c) Over Voltage Protection Latching type:105-110%
Current Limit	Yes
Start up time	750ms
Hold up time	37ms @230V AC
ENVIRONMENTAL	
Operating temperature upto 50 ⁰ C.	
Humidity	< 95% Rh
IP 21 Protection	
GENERAL	
Isolation	Input to Output – 1.5KV Input to Earth – 1.5KV Output to Earth- 500V
MTBF	50K Hrs to MIL
Efficiency	70%
INDICATIONS LED	a) Input OK b) Output OK c) Output OVP
MECHANICAL	
Dimension	135W X 90D X 50H mm
Cooling type	Natural
Weight	0.5 Kg